Insufflatoren
Insufflators
Insufflateurs
Insufladores
Insufflatori

Recommended for: **LAPAROSCOPY**



ON SCREEN DISPLAY *



TEKNO FLOW 15S	15 l/min	**tk 754-1509**	**tk 754-1509H**
TEKNO FLOW 20S	20 l/min	**tk 754-1512**	**tk 754-1512H**
TEKNO FLOW 30S	30 l/min	**tk 754-1522**	**tk 754-1522H**
TEKNO FLOW 45S	45 l/min	**tk 754-1532**	**tk 754-1532H**
	max. Gasflußrate *max. gas flow*	ohne CO_2 Heizung *without CO_2 heater*	mit CO_2 Heizung *with CO_2 heater*

Insufflatoren aus der TEKNO FLOW S Serie sind sehr solide und zuverlässig und entsprechen dem neuesten Stand der Technik.

Intuitive Bedienbarkeit, sowie gut ablesbare Anzeigen zeichnen diese Geräte aus. Neben der Versorgung durch Flaschengas ist auch der Betrieb über eine zentrale Gasversorgung möglich.

Die Geräte verfügen über ein spezielles Programm für die Pre-Insufflation, welches mit geringem Insufflationsdruck in Verbindung mit hohem Gasfluss arbeitet. Durch die kontinuierliche Drucküberwachung wird ein Höchstmaß an Patientensicherheit gewährleistet.

Optional sind die Insufflatoren mit einem Heizsystem erhältlich. Zusätzlich verfügen die Geräte über eine Differenzdruckanzeige und ein optionales Modul zum Einblenden der Insufflationsdaten in das Monitorbild *(nur in Verbindung mit ausgewählten TEKNO Kameras möglich).

TEKNO FLOW S insufflators series are very solid, reliable and incorporate the state of art technology.

Intuitive operation and easy to read indicators are characteristics of these insufflators. Besides working with gas cylinders the operation is also possible with a central gas supply.

A special program for pre-insufflation, which works with low inflation, combined with high gas flow, insurance works by continuous monitoring of the pressure. Offering a maximum of patient security.

*The insufflators are optionally available with a heating system. In addition, the device has a differential pressure indicator and an optional module to show inflation data on the monitor *(only possible in combination with selected TEKNO cameras).*

Bei Bestellung bitte CO_2-Anschluss angeben! PIN INDEX (F/UK/NL) DIN (D/PL/E/JAP/GR) ISO 5145 (ITALY)
When ordering, please specify CO_2 connection! PIN INDEX (F/UK/NL) DIN (D/PL/E/JAP/GR) ISO 5145 (ITALY)