Archivierungssystem
Data storage
Système de documentation
Sistema de documentación
Sistema per documentazione



MC 170

tk 754-2903

Der einfache Weg zur Aufnahme von Standbildern medizinischer Abläufe in Standard Definition. Die Bilder werden direkt auf einen USB Stick, oder auf eine optionale Festplatte gespeichert. Nach der Aufnahme genügt es, den USB Stick mit einem Computer zu verbinden. Danach stehen die Aufnahmen bereit zum Betrachten, Archivieren, Bearbeiten, Versenden, etc. Das Gerät ist kompatibel zu allen Standard Definition Kameras. Das Metallgehäuse und die wasserdichte Front erlauben den Einsatz in OPs, auf Grund der kompakten Bauweise passt das Gerät auf jeden Trolley.

The easy way to capture standard definition still images of your medical procedures. Images are recorded directly to a USB flash drive or optional hard disc drive. After recording, the flash drive may be plugged into any computer. Pictures may now be viewed, archived, edited, shared, etc. The unit is compatible with all standard definition medical cameras. With its steel case and fluid resistant front panel, the unit is built to withstand the rigors of the OR, due to the compact dimensions the unit will fit on any cart.

Technische Daten

• LCD-Monitor	6,3 cm / 2 1/2" Farbdisplay (nur zur Navigation, nicht für Diagnosezwecke)
• Tasten	Dichte, flüssigkeitsresistente Folientasten
• Video Ein-/Ausgänge	PAL oder NTSC (über Menü wählbar) S-Video- oder Composite (BNC)-Anschlüsse
• USB	USB2.0, High-Speed, 1 Frontanschluss, 3 Anschlüsse auf der Rückseite
• Netzwerkbetrieb	10/100 Ethernet-Schnittstelle mittels Netzwerk-Aufrüstset (optional)
• Fußschalter/Auslöser	Freihändiges Aufnehmen 3,5 mm Standard-Miniklinkenstecker
• Abmessungen:	240 x 200 x 63 mm
• Gewicht:	ca. 1,7 kg
• Umgebung	Lagerung -40° bis +85° C Betrieb: -20° bis +40° C
• Stromversorgung	AC 100-240V 50/60Hz 3-polige Kaltgerätebuchse
• Datenträger	USB-Sticks oder externe USB-Festplatte
• Bildformate	JPEG, TIFF, PNG, DICOM
• Bildgröße	1280 x 1024, 1024 x 768, 800 x 600, 640 x 480 Pixel
• Sicherheitszertifikate	CE 93/42/EEC, IEC 60601-1:2005, ANSI/AAMI ES60601-1:2005, CAN/CSA C22.2 No.60601-1:2008, E361228, FCC Part 15, FDA Class 1, RoHS, PSE, GOST-R
• Inhalt	USB-Stick, Videokabel, Stromkabel, Gebrauchsanweisung

Technical data

• *LCD Monitor*	*6.3 cm / 2 1/2", color (for video confirmation only, not for diagnosis)*
• *Buttons*	*Sealed membrane, fluid resistant*
• *Video In/Out*	*PAL or NTSC format using S-video or composite BNC*
• *USB Support*	*USB2.0, high speed, 1 front connector, 3 rear connectors*
• *Networking*	*Ethernet 10/100 connection via Network Upgrade Kit (optional)*
• *Footswitch/ Trigger*	*Hands-free capture Standard 3.5mm mini jack*
• *Dimensions:*	*240 x 200 x 63mm / 9.5 x 7.9 x 2.5"*
• *Weight:*	*approx. 1.7 kg / 3lb 12oz*
• *Environmental*	*Storage: -40° to +85° C Operating: -20° to +40° C*
• *Power*	*AC 100-240V 50/60Hz 3-prong AC jack*
• *Media*	*USB flash drives or external USB hard drive*
• *Image Formats*	*JPEG, TIFF, PNG, DICOM*
• *Image Size*	*1280 x 1024, 1024 x 768, 800 x 600, 640 x 480 pixels*
• *Certifications*	*CE 93/42/EEC, IEC 60601-1:2005, ANSI/AAMI ES60601-1:2005, CAN/CSA C22.2 No.60601-1:2008, E361228, FCC Part 15, FDA Class 1, RoHS, PSE, GOST-R*
• *Kit Contents*	*USB flash drive, video cables, power cable, userguide*